

540,248

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number  
WO 2004/057148 A1

(51) International Patent Classification<sup>7</sup>: E21B 10/64

(21) International Application Number:  
PCT/FI2003/000982

(22) International Filing Date:  
23 December 2003 (23.12.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:  
20022276 23 December 2002 (23.12.2002) FI

(71) Applicant (for all designated States except US): ROBIT  
ROCKTOOLS LTD [FI/FI]; Vikkiniityntie 9, FIN-33880  
Lempäälä (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MATTILA, Mikko  
[FI/FI]; Iidesranta 24 B 36, FIN-33100 Tampere (FI).

(74) Agent: NIEMINEN, Taisto; Patenttitoimisto T Nieminen  
Oy, Kehräsaari B, FIN-33200 Tampere (FI).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BIT ASSEMBLY



(57) Abstract: A bit assembly for a drilling apparatus working by impact and rotation or merely by rotation, and comprising a pilot bit (1) drilling the hole centre and in connection with the pilot bit a ring bit (2) is arranged to drill the outer circle of the hole and, further, between pilot bit and ring bit surfaces are arranged to transmit impacts and/or rotary motion from the pilot bit to the ring bit, and the bit assembly also including an arrangement for pulling protectino tube into the hole on drilling. In the bit assembly between ring bit (2) and pilot bit (1) at least an arrangement transmitting rotation is jointly fitted in the ring bit shirt portion (5) by forming the rear edge of the shirt portion seen in the drilling direction to comprise surfaces with different directions, which with one of their portion (4) can transmit rotary motion force to the ring bit (2) and with their adjacent part (3) force to pull said ring bit off the hole.

WO 2004/057148 A1